

# **Accepted Road Safety Barrier Systems and Devices**

Issue date: 12 April 2023

Effective date: 12 April 2023

## Disclaimer

This document has been prepared by Transport for NSW (TfNSW) specifically for its own use and is also available for use by NSW public transport agencies for transport assets.

Any third parties considering use of this document should obtain their own independent professional advice about the appropriateness of using this document and the accuracy of its contents. TfNSW disclaims all responsibility and liability arising whether directly or indirectly out of or in connection with the contents or use of this document.

TfNSW makes no warranty or representation in relation to the accuracy, currency or adequacy of this document or that the document is fit for purpose.

The inclusion of any third party material in this document, does not represent an endorsement by TfNSW of any third party product or service.

For queries regarding this document, please email Transport for NSW Advanced Technical Services at [technologystandards@transport.nsw.gov.au](mailto:technologystandards@transport.nsw.gov.au)

## Document information

**Owner:** Director Corridor Infrastructure and Engineering  
Asset Management  
Safety, Environment and Regulation

**Mode:** Active

**Discipline:** Traffic

## Document history

Revision	Effective date	Summary of changes
1.0	7 July 2022	First issue.
2.0	12 October 2022	Second issue. Update in line with outcomes from the August 2022 ASBAP meeting.
3.0	20 February 2023	Third issue. Update in line with outcomes from the November 2022 ASBAP meeting.
4.0	12 April 2023	Fourth issue. Update in line with outcomes from the February 2023 ASBAP meeting.

## Preface

This document provides a list of road safety barrier systems and devices that TfNSW has assessed as meeting the requirements of AS/NZS 3845 and considers acceptable for use on the classified road network, subject to appropriate design and installation. For roads not on the classified road network (for example, local roads), the responsible road authority (for example, councils) should be contacted to determine if this list is applicable.

## Table of contents

<b>1</b>	<b>Scope .....</b>	<b>6</b>
<b>2</b>	<b>Application .....</b>	<b>6</b>
<b>3</b>	<b>Referenced documents .....</b>	<b>6</b>
<b>4</b>	<b>Terms, definitions and abbreviations .....</b>	<b>7</b>
<b>5</b>	<b>Assessment process .....</b>	<b>8</b>
<b>6</b>	<b>Austrroads Technical Conditions of Use (TCU)and TfNSW conditions .....</b>	<b>8</b>
<b>7</b>	<b>System supplier and procurement.....</b>	<b>8</b>
<b>8</b>	<b>Accepted test level .....</b>	<b>8</b>
<b>9</b>	<b>ASBAP technical advice notes .....</b>	<b>9</b>
<b>10</b>	<b>Frequently asked questions .....</b>	<b>9</b>
10.1	Installation on a kerb – permanent systems .....	9
10.2	Installation on a kerb – temporary systems .....	9
10.3	Foundation and pavement conditions .....	9
10.4	Minimum installation length.....	10
10.5	Attachments and screens.....	10
10.6	Offset to hazards.....	10
10.7	Proximity to the batter hinge .....	10
10.8	Distance to an excavation .....	11
<b>11</b>	<b>Accepted products .....</b>	<b>11</b>
11.1	Accepted permanent products .....	11
11.2	Accepted temporary products .....	18
11.3	Other crashworthy devices.....	24
11.4	Permanent products – legacy status.....	26
11.5	Temporary products – legacy status.....	28

# 1 Scope

This document covers road safety barrier systems and devices. The systems and devices listed in this document are those that TfNSW has assessed as meeting the requirements of AS/NZS 3845 and considers acceptable for use on the classified road network, subject to appropriate design and installation. For roads not on the classified road network (for example, local roads), the responsible road authority (for example, councils) should be contacted to determine if this list is applicable.

# 2 Application

Safety barrier selection and design is an intricate process that requires the application of engineering judgement and risk assessment. Designers should use this list of accepted road safety barrier systems and devices in conjunction with:

- *Austrroads Guide to Road Design Part 6: Roadside Design, Safety and Barriers* which describes the steps involved in designing a safety barrier installation
- TfNSW specification R132 *Safety Barrier Systems*
- the Austrroads Technical Conditions for Use (TCU) documents and TfNSW specific conditions or variants listed in this document, which detail any product specific limitations identified through assessment
- the individual product installation and maintenance manuals, which are provided by the product owner or supplier to help achieve the desirable installation.

For further information regarding the product assessment and barrier performance, refer to the Austrroads Barrier Assessment webpages <https://austrroads.com.au/safety-and-design/barrier-assessment>

Where reference to TfNSW accepted products, this document should be deemed to satisfy that requirement.

For further clarification, please contact [TechnologyStandards@Transport.nsw.gov.au](mailto:TechnologyStandards@Transport.nsw.gov.au)

# 3 Referenced documents

The following documents are cited in the text. For dated references, only the cited edition applies. For undated references, the latest edition of the referenced document applies.

## **International standards**

AASHTO MASH 2: 2016 *Manual for Assessing Safety Hardware*

### **Australian standards**

AS/NZS 3845.1:2015 *Road safety barrier systems and devices – Part 1: Road safety barrier systems*

AS/NZS 3845.2:2017 *Road safety barrier systems and devices – Part 2: Road safety devices*

### **Transport for NSW standards**

11.097 *Supplement to Austroads Guide to Road Design Part 6: Roadside Design, Safety and Barriers* (2009), version 2.0

R132 *Safety Barrier Systems*

*Traffic Control at Work Sites Technical Manual*

### **Other referenced documents**

Austroads 2009, *Guide to Road Design – Part 6: Roadside Design, Safety and Barriers*

Note: TfNSW has not yet adopted the latest issue of Part 6 of the guide.

## **4 Terms, definitions and abbreviations**

The following terms, definitions and abbreviations apply in this document.

**accepted** accepted for use on the classified road network

**AGRD** The Austroads Guide to Road Design – Part 6

**ASBAP** Austroads Safety Barrier Assessment Panel

**CA** crashworthiness assessment

**conditionally accepted status** allows products to remain in service with specific conditions

**legacy status** for permanent products allows retention of permanent products until the end of service life; for temporary products allows the product to be used on contracts signed on or before 1 January 2022

**MASH** Manual for Assessing Safety Hardware

**phase out status** allows products to remain in service to a fixed date after which time it will be withdrawn from acceptance

**TCAWS** Traffic Control at Work Sites Technical Manual

**TCU** technical conditions for use

**TfNSW** Transport for NSW

**WRSB** wire rope safety barrier

## 5 Assessment process

The assessment of road safety barrier systems, end treatments, and related road safety devices is undertaken at a national level by the Austroads Safety Barrier Assessment Panel (ASBAP).

Where an assessment by ASBAP results in a recommendation for acceptance, the recommendation together with any conditions of acceptance is documented by Austroads.

Following the recommendation, TfNSW will determine if the recommendation is suitable for the NSW classified road network.

## 6 Austroads Technical Conditions of Use (TCU) and TfNSW conditions

To improve national harmonisation, the Austroads Technical Conditions of Use (TCU) will be adopted by TfNSW when deemed suitable. Where Austroads has issued multiple revisions of a TCU, the revision specified and linked in this document shall be adopted.

Where TfNSW has specific conditions or variants, they will be detailed in the relevant column in the relevant table in this document. Where TfNSW does not have additional product conditions or variants, this column will contain 'Nil' and the Austroads TCU shall be adopted in its entirety.

In special circumstances, TfNSW may accept a road safety product that has not been assessed by ASBAP and therefore does not have an Austroads TCU. In this instance TfNSW acceptance conditions will be provided and referenced.

All products accepted for use by TfNSW are listed in this document. Using a product that is not accepted or using a product outside the parameters for which it has been accepted by TfNSW represents additional risk, and requires a site-specific risk assessment to determine suitability.

TfNSW will periodically review all products accepted for use based on, but not limited to, ASBAP recommendations, in-service performance, industry use, and maintenance and durability requirements and reserves the right to withdraw or modify acceptances at any time.

## 7 System supplier and procurement

This listing nominates a system supplier for each proprietary product. It is a requirement of TfNSW that proprietary products are sourced from the nominated system supplier (or their agent).

## 8 Accepted test level

The minimum test level required for a site shall be determined using engineering judgement and information obtained during site-specific assessment. Further guidance is provided in *Guide to Road Design – Part 6: Roadside Design, Safety and Barriers*.



## 9 ASBAP technical advice notes

ASBAP provides technical advice notes to inform road agencies on issues related to safety barrier systems and devices. The webpage for technical advice notes is:  
<https://austroads.com.au/safety-and-design/barrier-assessment/technical-service>

## 10 Frequently asked questions

### 10.1 Installation on a kerb – permanent systems

Permanent safety barriers should not be installed on a kerb as, upon vehicle impact, roll and pitch are developed which can affect the interaction of the vehicle with the barrier. This is more likely to occur where vehicle speeds exceed 70 km/h.

Where installation on top of a kerb is required, the barrier should be offset either:

- a. far enough behind the kerb to allow an errant vehicle to stabilise after crossing the kerb before striking the barrier (desirably 1.5 metres)
- b. close enough to the kerb so an impacting vehicle has not had adequate time to develop significant pitch and/or roll; it is important that enough offset from the kerb is provided for the foundation of the barrier to be constructed (desirably 200 mm).

### 10.2 Installation on a kerb – temporary systems

Temporary barriers, including end treatments, should not be installed immediately in front of or behind kerbs on roads with a posted speed of 70 km/h or more, irrespective of profile. Special consideration may be given to placement of the temporary barrier system on top of a mountable or semi-mountable kerb where a site risk assessment has determined the site constraints preclude other options. The barrier shall not be placed where it could contact the kerb within its normal deflection range for the speed environment.

On roads with a posted speed of 60 km/h or less, temporary road safety barrier systems may be placed on top of the kerb. A site risk assessment should be completed to consider the impacts the kerb will have on the impact height and angle of an errant vehicle. The barrier shall not be placed where it could contact the kerb within its normal deflection range for the speed environment.

### 10.3 Foundation and pavement conditions

Safety barrier systems rely on adequate foundation strength to perform successfully. Therefore, it is important that site ground conditions are verified and confirmed to be at least as good as tested conditions. Where the ground conditions vary, it may be necessary to either amend the foundation design in accordance with the design/installation guidance provided by the system supplier or consider an alternative system.

## 10.4 Minimum installation length

While barrier lengths shorter than the tested article length shown in the Austroads TCUs are possible, the designer shall consider how this will affect other performance values (such as deflection). Additional commentary can be found in *Guide to Road Design – Part 6: Roadside Design, Safety and Barriers*.

## 10.5 Attachments and screens

In accordance with the requirements of Australian/New Zealand standard AS/NZS 3845 there shall be no attachment to a road safety barrier system unless it can be shown by crash testing or risk assessment to be suitable.

At present there are no road furniture items such as headlight screens, signs, lighting posts, fences, visual screens, debris screens, pedestrian/cyclist rails, and so on, permitted to be attached to road safety barrier systems.

## 10.6 Offset to hazards

Appropriate clearance shall be allowed between the safety barrier and the hazard that it is protecting to allow for either the accepted deflection or the working width of the barrier when impacted, dependent upon whether the hazard is above or below the road surface level.

Where the hazard will not be impacted by any part of the vehicle that extends beyond the barrier, generally where the hazard is below road surface level (for example, fill batter), the 'accepted deflection' is sufficient.

Where the hazard may be impacted by any part of the vehicle that extends beyond the barrier, generally where the hazard is above road surface level, 'working width' shall be used.

## 10.7 Proximity to the batter hinge

Safety barriers should be installed with sufficient distance to the hinge point to accommodate the barrier's accepted dynamic deflection and to provide adequate lateral support for the system. This ensures that there is no damage to the batter following an impact and that the lateral support for the system is adequate to achieve the tested conditions.

Where the site is constrained, it may be possible to place the barrier closer to the hinge point. Issues such as constructability, performance of the product, impact on posts/anchorage and space behind batter for workers need to be addressed. This may involve the use of longer posts or other treatments to ensure that there is sufficient lateral support for the barrier system.

Maintenance of the barrier and the area behind the barrier may be difficult and appropriate maintenance procedures should be considered and documented as part of the installation requirements.

## 10.8 Distance to an excavation

The minimum distance between the back of the system and the edge of an excavation should provide sufficient distance to accommodate the barrier's design deflection and provide adequate lateral support for the system, whichever is the greater.

## 11 Accepted products

### 11.1 Accepted permanent products






MASH TL3 and TL4 permanent products are accepted for use in 110 km/h speed zones.







#### 11.1.1 Steel rail safety barriers

Due to the performance of steel rail safety barriers during impact, that is, flattening of the rail, the dynamic deflection and working width values at TL3 are generally the same. At TL4 the working width value includes any heavy vehicle roll observed during testing.

Steel rail safety barriers are listed in Table 1.

**Table 1 – Steel rail safety barriers**

Product name	Supplier	Austroads TCU	Test level	Product photo	TfNSW conditions & variants
CrocGuard Safety Barrier	Safe Direction	9 Jun 22	MASH TL4 MASH TL3		Nil
EZY-GUARD High Containment Safety Barrier	Ingal Civil Products	1 Dec 22	MASH TL4 MASH TL3		Nil
EZY-GUARD LDS Safety Barrier	Ingal Civil Products	15 Dec 22	MASH TL4 MASH TL3		Nil
RAMSHIELD High Containment Safety Barrier	Safe Direction	8 Dec 22	MASH TL4 MASH TL3		Nil
Sentry Thrie-Beam Safety Barrier	Australian Construction Products	14 Mar 22	MASH TL4 MASH TL3		Nil

Product name	Supplier	Austrroads TCU	Test level	Product photo	TfNSW conditions & variants
EZY-GUARD 4 Safety Barrier	Ingal Civil Products	<i>3 April 23</i>	MASH TL3		Nil
EZY-GUARD Smart Safety Barrier	Ingal Civil Products	<i>15 Sep 22</i>	MASH TL3		Nil
EZY-GUARD HD Safety Barrier	Ingal Civil Products	<i>2 Mar 23</i>	MASH TL3		Nil
RAMSHIELD Safety Barrier	Safe Direction	<i>15 Sep 22</i>	MASH TL3		Nil
SENTRY W BEAM Safety Barrier	Australian Construction Products	<i>20 Mar 23</i>	MASH TL3		Nil
NSW Transition to Rigid Concrete	Public Domain	Not applicable	NCHRP 350		Conditionally accepted <i>1 Jan 20</i>

### 11.1.2 Wire rope safety barriers

The following apply to all wire rope safety barriers (WRSB):



- a. The maximum length of WRSB between anchors is 1000 m where this is in accordance with the system owner's and system supplier's guidance. Longer installations require intermediate anchorage. It is necessary to overlap the intermediate anchors to provide a continuous length of redirective barrier system. A minimum of accepted deflection distance should be provided between the intermediate anchors. This minimises any risk associated with errant vehicles impacting two systems simultaneously which is not well understood at this time.
- b. WRSB consist of tensioned ropes held between posts and, as such, there is a limit to their use on horizontal and vertical alignments. It is generally accepted that the minimum allowable horizontal curve radius for WRSB installations is 200 m, however if the system

supplier specifies a minimum that is different than this, the manufacturer's requirements shall be used. The minimum allowable sag curve K value is 30. The use of intermediate anchors at the base of sag curves may be considered to reduce ropes from rising. There is no K value limit for crest curves.

- c. It has been demonstrated that the deflection of WRSB will continually increase as the length of installation increases. It is therefore necessary to multiple the accepted deflection distances by correction factors to determine the appropriate design deflection for an installation. The correction factors are published in the product manuals for individual proprietary WRSB.

Wire rope safety barriers are listed in Table 2.


**Table 2 – Wire rope safety barriers**

<b>Product name</b>	<b>Supplier</b>	<b>Austroads TCU</b>	<b>Test level</b>	<b>Product photo</b>	<b>TfNSW conditions &amp; variants</b>
MashFlex Wire Rope Safety Barrier	Ingal Civil Products	<i>14 Mar 22</i>	MASH TL4 MASH TL3		Nil
Sentryline-M Wire Rope Safety Barrier	Australian Construction Products	<i>3 Sep 21</i>	MASH TL4 MASH TL3		Nil
Brifen Wire Rope Safety Barrier	Safe Direction	<i>20 Nov 20</i>	MASH TL3		Nil

### 11.1.3 Steel safety barriers

Steel safety barriers are listed in Table 3.

**Table 3 – Steel safety barriers**


<b>Product name</b>	<b>Supplier</b>	<b>Austroads TCU</b>	<b>Test level</b>	<b>Product photo</b>	<b>TfNSW conditions &amp; variants</b>
HighwayGuard Safety Barrier	Ingal Civil Products	<i>8 Sep 22</i>	MASH TL4 MASH TL3		Nil

Product name	Supplier	Austrroads TCU	Test level	Product photo	TfNSW conditions & variants
HighwayGuard LDS Safety Barrier	Ingal Civil Products	<i>1 Dec 21</i>	MASH TL3 MASH TL4		Nil
SafeZone LDS Safety Barrier	Jaybro Group	<i>21 Jun 22</i>	MASH TL4 MASH TL3		Nil
SafeZone Safety Barrier	Jaybro Group	<i>21 Jun 22</i>	MASH TL4 MASH TL3		Nil
BG800 Safety Barrier	Highway Care	<i>14 Mar 22</i>	MASH TL4 MASH TL3		Nil
BG800 MDS Safety Barrier	Highway Care	<i>1 Dec 21</i>	MASH TL3		Nil
BG800 LDS Safety Barrier	Highway Care	<i>2 Sep 22</i>	MASH TL2 (Modified) 80km/h		Nil

### 11.1.4 Concrete safety barriers

TfNSW does not accept the use of precast concrete barriers for permanent use. Concrete safety barriers are listed in Table 4.



**Table 4 – Concrete safety barriers**

Product name	Supplier	Austrroads TCU	Test level	Product photo	TfNSW conditions & variants
TYPE F Concrete Safety Barrier	Public Domain	Not applicable	MASH TL5 MASH TL4 MASH TL3		<i>4 Apr 23</i>

### 11.1.5 Other safety barriers

Other safety barriers are listed in Table 5.

**Table 5 – Other safety barriers**




<b>Product name</b>	<b>Supplier</b>	<b>Austrroads TCU</b>	<b>Test level</b>	<b>Product photo</b>	<b>TfNSW conditions &amp; variants</b>
QUICKCHANGE Concrete Reactive Tension Barrier System	Lindsay Transportation Services	<i>3 Sep 21</i>	MASH TL3		Nil
SAFETY ROLLER Safety Barrier	Australian Construction Products	<i>4 Apr 23</i>	MASH TL4 MASH TL3		Nil




### 11.1.6 Terminals

A gating terminal is designed to permit controlled penetration of errant vehicles behind the system. A run out area should be provided to allow adequate space for the vehicle to safely come to rest. Unless otherwise specified in the TCU documents, the run out area should be 18.5 m in length x 6 m in width (from the point of redirection). Run out areas should have a crossfall of 10:1 or flatter and be free of roadside hazards.

Terminals are listed in Table 6.

**Table 6 – Terminals**

<b>Product name</b>	<b>Supplier</b>	<b>Austrroads TCU</b>	<b>Test level</b>	<b>Product photo</b>	<b>TfNSW conditions &amp; variants</b>
ET-SS Terminal	Ingal Civil Products	<i>1 Dec 22</i>	MASH TL3 MASH TL2		Nil
MAX-TENSION Terminal	Australian Construction Products	<i>14 Mar 22</i>	MASH TL3 MASH TL2		Nil
MSKT (MASH Sequential Kinking Terminal)	Safe Direction	<i>7 Jun 21</i>	MASH TL3 MASH TL2		Nil




Product name	Supplier	Austroads TCU	Test level	Product photo	TfNSW conditions & variants
Trend Median Terminal	Ingal Civil Products	<i>24 Mar 23</i>	MASH TL3		Nil
TRAILING Terminal	Public Domain	Not applicable	MASH TL3		<i>31 Jan 20</i>
SLOPED END Concrete Terminal – Permanent	Public Domain	Not applicable	70 km/h		<i>6 Jul 21</i>

### 11.1.7 Redirective crash cushions



Redirective crash cushions are not to be deployed as single point protectors for traffic signal posts without approval from the relevant Transport for NSW representative.

Redirective crash cushions are listed in Table 7.

**Table 7 – Redirective crash cushions**

Product name	Supplier	Austroads TCU	Test level	Product photo	TfNSW conditions & variants
HERCULES Crash Cushion	Safe Direction	<i>2 Mar 23</i>	MASH TL3		Nil
QUADGUARD Elite M10 Crash Cushion	Ingal Civil Products	<i>18 Dec 20</i>	MASH TL3		Nil
QUADGUARD M10 Crash Cushion	Ingal Civil Products	<i>4 Mar 21</i>	MASH TL3 MASH TL2		Nil







Product name	Supplier	Austrroads TCU	Test level	Product photo	TfNSW conditions & variants
SMART Crash Cushion	HS Roads	<i>20 May 22</i>	MASH TL3 MASH TL2		Nil
UNIVERSAL TAU-M Crash Cushion	Australian Construction Products	<i>4 Mar 21</i>	MASH TL3 MASH TL2		Nil

### 11.1.8 Median gates

In line with the changes to AS/NZS 3845 and the recommendation of the ASBAP, TfNSW has transitioned the current suite of accepted safety barrier systems and devices to the MASH test protocol. MASH tested products provide an increased level of safety to road users. As of 1 January 2022, the products in Table 8 will be 'conditionally accepted' until such time as a MASH tested horizontal longitudinal safety barrier gate is recommended for use.

**Table 8 – Median gates**

Product name	Supplier	Austrroads TCU	Test level	Product photo	TfNSW conditions & variants
ARMORGUARD Gate	Australian Construction Products	<i>20 Nov 20</i>	NCHRP 350 TL3		Conditionally accepted
BG800 Gate	Ingal Civil Products	<i>20 Nov 20</i>	NCHRP 350 TL3		Conditionally accepted
VEVA3 Median Gate	Traffic Tech	<i>20 Nov 20</i>	EN1317 HC2		Conditionally accepted
Cado Emergency Gate	Traffic Tech	<i>2 Sep 22</i>	MASH TL3		Nil

## 11.1.9 Bollards and point protectors

Bollards and point protectors are listed in Table 9.

**Table 9 – Bollards and point protectors**

Product name	Supplier	Austrroads TCU	Test level	Product photo	TfNSW conditions & variants
ENERGY Absorbing Bollard	Roadside Services & Solutions Impact Absorbing Systems	Not applicable	50 km/h		<i>Oct 18</i>
OMNI STOP Ultra Security Bollard	SafeRoads	Not applicable	50 km/h		<i>25 May 18</i>
RAPTOR Plastic Single Point Protector	Valmont Highway	<i>1 Dec 21</i>	50 km/h		Nil

## 11.2 Accepted temporary products

A temporary safety barrier is defined as a road safety barrier that is installed in association with adjacent ongoing and continuous works, short term emergencies, or similar situations. This type of safety barrier shall be removed upon completion of the works or emergency. Temporary safety barriers perform in the same way as other road safety barriers; however, the consequence of a failure of the barrier may involve injury to road workers.





When choosing a temporary safety barrier it is necessary to consider the speed environment during works and periods of in-activity. If it is likely higher speeds will be realised (or permitted) during periods of in-activity, a safety barrier approved for the higher speed zone shall be chosen.

### 11.2.1 Concrete safety barriers

Concrete safety barriers are listed in Table 10.

**Table 10 – Concrete safety barriers**




Product name	Supplier	Austrroads TCU	Test level	Product photo	TfNSW conditions & variants
Rebloc 120FA_6_SF Safety Barrier	Hill & Smith	<i>16 Jun 22</i>	MASH TL 5 MASH TL 3		Nil
DB80 T150 Safety Barrier	Orange Hire	<i>20 Dec 21</i>	MASH TL4 MASH TL 3		Nil
Rebloc 80SAH_12	Hill & Smith	<i>2 Sep 22</i>	MASH TL4 MASH TL3		Nil
3.6M JJ Hooks Safety Barrier – Freestanding	Australian Road Barriers	<i>14 Mar 22</i>	MASH TL3		Nil
6M JJ HOOKS Safety Barrier	Australian Road Barriers	<i>14 Mar 22</i>	MASH TL3		Nil
DB80 K150 Safety Barrier	Orange Hire	<i>20 Jul 21</i>	MASH TL3		Nil
DB80A T150S Safety Barrier	Orange Hire	<i>1 Dec 21</i>	MASH TL3		Nil
PIN and LOOP LDS Safety Barrier	Pin and Loop	<i>21 Jan 21</i>	MASH TL3		Nil
PIN and LOOP Safety Barrier	Pin and Loop	<i>1 Dec 21</i>	MASH TL3		Nil


Product name	Supplier	Austrroads TCU	Test level	Product photo	TfNSW conditions & variants
Rebloc 80SAH_12_8B	Hill & Smith	<a href="#">22 Mar 22</a>	MASH TL3		Nil
Rebloc 80SAH_4	Hill & Smith	<a href="#">1 Dec 22</a>	MASH TL3		Nil
T-LOK F-TYPE Safety Barrier	Saferoads	<a href="#">2 Sep 22</a>	MASH TL3		Nil
T-LOK Rubber Safety Barrier	Saferoads	<a href="#">24 Mar 23</a>	MASH TL3		Nil



## 11.2.2 Steel safety barriers

Steel safety barriers are listed in Table 11.

**Table 11 – Steel safety barriers**

Product name	Supplier	Austrroads TCU	Test level	Product photo	TfNSW conditions & variants
BG800 Safety Barrier	Highway Care	<a href="#">2 Mar 23</a>	MASH TL4 MASH TL3		Nil
DEFENDER 100 HC Safety Barrier	Safe Barriers	<a href="#">28 Apr 22</a>	MASH TL4 MASH TL3		Nil
HighwayGuard LDS Safety Barrier	Ingal Civil Products	<a href="#">1 Dec 22</a>	MASH TL4 MASH TL3		Nil

Product name	Supplier	Austrroads TCU	Test level	Product photo	TfNSW conditions & variants
HighwayGuard Safety Barrier	Ingal Civil Products	1 Dec 22	MASH TL4 MASH TL3		Nil
SafeZone LDS Safety Barrier	Jaybro Group	21 Jun 22	MASH TL4 MASH TL3		Nil
SafeZone SafetyBarrier	Jaybro Group	21 Jun 22	MASH TL4 MASH TL3		Nil
BG800 MDS Safety Barrier	Highway Care	2 Mar 23	MASH TL3		Nil
DEFENDER 100 FS Safety Barrier	Safe Barriers	1 Dec 21	MASH TL3		Nil
DEFENDER 100 LDS Safety Barrier	Safe Barriers	28 Apr 22	MASH TL3		Nil
ZONEGUARD MDS Safety Barrier	Hill & Smith	1 Dec 22	MASH TL3		Nil
ZONEGUARD Safety Barrier	Hill & Smith	2 Mar 23	MASH TL3		Nil
BG800 LDS Safety Barrier	Highway Care	2 Mar 23	MASH TL2 (Modified) 80km/h		Nil
DEFENDER 70 Safety Barrier	Safe Barriers	1 Dec 21	MASH TL2		Nil

Product name	Supplier	Austrroads TCU	Test level	Product photo	TfNSW conditions & variants
HV2 Hybrid Safety Barrier	Saferoads	<i>1 Dec 21</i>	MASH TL4 MASH TL3		Nil
IRONMAN HYBRID Safety Barrier	Saferoads	<i>17 Sep 21</i>	MASH TL3		Nil

### 11.2.3 Plastic water filled safety barriers

Plastic water filled safety barriers are listed in Table 12.



**Table 12 – Plastic water filled safety barriers**

Product name	Supplier	Austrroads TCU	Test level	Product photo	TfNSW conditions & variants
ARMORZONE MASH Plastic Water Filled System	Ingal Civil Products	<i>20 Nov 20</i>	MASH TL2 MASH TL1		Nil
Lo-Ro Water Cable Barrier	Jaybro Group	<i>20 Nov 20</i>	MASH TL2 MASH TL1		Nil
RICOCHET Plastic Water Filled System	TFH Hire Services	<i>20 Nov 20</i>	MASH TL1		Nil
SHIELD I Plastic Water Filled System	National Plastics	<i>20 Nov 20</i>	MASH TL1		Nil

### 11.2.4 Other safety barriers

Other safety barriers are listed in Table 13.

**Table 13 – Other safety barriers**

Product name	Supplier	Austrroads TCU	Test level	Product photo	TfNSW conditions & variants
MOBILE BARRIERS MBT-1 Safety Barrier	Dynamic Road Maintenance Services	<i>20 Nov 20</i>	MASH TL3 Speed restricted 80 km/h		Nil
QUICKCHANGE Concrete Reactive Tension Barrier System	Lindsay Transportation Services	<i>3 Sep 21</i>	MASH TL3		Nil

### 11.2.5 Water-filled crash cushions

Water-filled crash cushions are non-redirective devices that gate during impact. A gating end treatment is designed to permit controlled penetration of errant vehicles behind the system. A run out area should be provided to allow adequate space for the vehicle to safely come to rest. Unless otherwise specified in the TCU, the run out area should be 18.5 m in length x 6 m in width (from the point of redirection). Run out areas should have a crossfall of 10 to 1 or flatter and be free of roadside hazards.

Water-filled crash cushions are listed in Table 14.

**Table 14 – Water-filled crash cushions**

Product name	Supplier	Austrroads TCU	Test level	Product photo	TfNSW conditions & variants
ABSORB-M Crash Cushion	Australian Construction Products	<i>7 Jun 21</i>	MASH TL3 – Speed Restricted 80km/h MASH TL2		Nil
SLED Plastic Water Filled Terminal	Saferoads Pty Ltd	<i>5 Dec 20</i>	MASH TL3 – Speed Restricted 80km/h MASH TL2 MASH TL1		Nil
ArmorBuffa Crash Cushion	Ingal Civil Products	<i>2 Mar 23</i>	MASH TL3 – Speed Restricted 80km/h		Nil

## 11.2.6 Redirective crash cushions

Redirective crash cushions are listed in Table 15.

**Table 15 – Redirective crash cushions**

Product name	Supplier	Austrroads TCU	Test level	Product photo	TfNSW conditions & variants
HERCULES Crash Cushion	Safe Direction	<i>2 Mar 23</i>	MASH TL3		Nil
QUADGUARD M10 CZ Crash Cushion	Ingal Civil Products	<i>6 Sep 21</i>	MASH TL3 MASH TL2		Nil
SMART Crash Cushion	HS Roads	<i>20 May 22</i>	MASH TL3 MASH TL2		Nil
UNIVERSAL TAU-M Crash Cushion	Australian Construction Products	<i>4 Mar 21</i>	MASH TL3 MASH TL2		Nil

## 11.3 Other crashworthy devices



The products in this list have been assessed and recommended by ASBAP in accordance with AS/NZS 3845.2:2017. Products listed here have only been assessed in accordance with AS/NZS 3845.2:2017, and there are other approvals that are required elsewhere in the organisation prior to use. In other words, a product listed here has been deemed to be crashworthy but this is not the only consideration. Users should select devices which are fit for purpose to their total requirements, noting that crashworthiness is just one aspect to consider.

### 11.3.1 Sign support structures and poles

Sign support structures and poles are listed in Table 16



**Table 16 – Sign support structures and poles**

Product name	Supplier	Austrroads CA	Test level	Product photo	TfNSW conditions & variants
OPTIMAST Sign Support	Delnorth Group	<i>20 Dec 21</i>	MASH TL3		Nil
SIGNFIX Sign Support	Delnorth Group	<i>20 Dec 21</i>	MASH TL3		Nil


### 11.3.2 Truck and trailer mounted attenuators

All activities utilising truck or trailer mounted attenuators shall be undertaken in accordance with TCAWS and supported by a risk assessment that is specific to the tasks being undertaken.

Truck and trailer mounted attenuators are listed in Table 17.

**Table 17 – Truck and trailer mounted attenuators**

Product name	Supplier	Austrroads CA	Test level	Product photo	TfNSW conditions & variants
MASH Scorpion II TL3 Trailer Attenuator	A1 Roadlines	<i>20 Nov 20</i>	MASH TL3		Nil
SCORPION II MASH Truck Mounted Attenuator	A1 Roadlines	<i>20 Nov 20</i>	MASH TL3		Nil
Silke MASH Truck Mounted Attenuator	J1-Led Intelligent Solutions	<i>22 Mar 22</i>	MASH TL3		Nil
SS180M TMA	Ingal Civil Products	<i>20 Nov 20</i>	MASH TL3		Nil

Product name	Supplier	Austrroads CA	Test level	Product photo	TfNSW conditions & variants
TTMA-200 Trailer Mounted Attenuator	Gregory Industries	4 Mar 21	MASH TL3		Nil
VERDEGRO BLADE Truck Mounted Attenuator	Innov8 Equipment	5 Dec 20	MASH TL3		Nil
MASH Scorpion II TL2 TMA	A1 Roadlines	20 Nov 20	MASH TL2		Nil

## 11.4 Permanent products – legacy status

There shall be no installations of permanent products with legacy status.

AS/NZS 3845.1:2015 and AS/NZS 3845.2:2017 specify MASH as the current basis for crash testing, thereby superseding NCHRP 350. The changes are in response to the ongoing industry progress, market trends, and changes in the average vehicle size, plus an increased availability of MASH tested products becoming available to the Australian market.


Safety barrier systems with a legacy status continue to provide the level of service at which they were originally tested. Legacy status products may be maintained and/or repaired until the end of their service life, or when parts are no longer available.

When long lengths of legacy items are damaged or within the limit of works, an assessment should be made on whether an approved system may be installed instead as part of reinstatement works.

Legacy products shall not be relocated.

Permanent products with legacy status are listed in Table 18.

**Table 18 – Permanent products – legacy status**

Product name	Supplier	Acceptance conditions date	Product photo
ET 2000 PLUS Terminal	Ingal Civil Products	1 Jan 20	

<b>Product name</b>	<b>Supplier</b>	<b>Acceptance conditions date</b>	<b>Product photo</b>
FLEAT 350 Terminal	Safe Direction	<i>Aug 14</i>	
FLEAT-SP Terminal	Safe Direction	<i>1 Jan 20</i>	
FLEXFENCE TL3 3 Wire Rope Barrier System	Ingal Civil Products	<i>Aug 14</i>	
FLEXFENCE TL3 4 Wire Rope Barrier System	Ingal Civil Products	<i>1 Jan 20</i>	
FLEXFENCE TL4 4 Wire Rope Barrier System	Ingal Civil Products	<i>1 Oct 20</i>	
IRONMAN MEDIAN Gate	Saferoads	<i>Jan 15</i>	
MELT (MODIFIED ECCENTRIC LOADER TERMINAL) Steel Rail Terminal	Public Domain	<i>7 Jun 19</i>	
QUADGUARD Crash Cushion – Permanent	Ingal Civil Products	<i>1 Jan 20</i>	
Rubber Crash Cushion	Saferoads	<i>Aug 14</i>	
SENTRYLINE II 4 Wire Rope Barrier System	Australian Construction Products	<i>1 Oct 20</i>	
SKT 350 Terminal	Safe Direction	<i>Jun 14</i>	
SKT-SP Terminal	Safe Direction	<i>1 Jan 20</i>	

Product name	Supplier	Acceptance conditions date	Product photo
THRIE-BEAM Safety Barrier	Public Domain	1 Jan 20	
TRACC Crash Cushion	Ingal Civil Products	1 Jan 20	
TREND 350 Terminal	Ingal Civil Products	1 Jan 20	
UNIVERSAL TAU-II Crash Cushion – Permanent	Australian Construction Products	1 Jan 20	
W-BEAM G4 Safety Barrier	Public Domain	1 Jan 20	
X-TENSION 350 Terminal	Australian Construction Products	1 Jan 20	

## 11.5 Temporary products – legacy status

There shall be no temporary products with legacy status used on contracts signed post 1 January 2022.

AS/NZS 3845.1:2015 and AS/NZS 3845.2:2017 specify MASH as the current basis for crash testing, thereby superseding NCHRP 350. The changes are in response to the ongoing industry progress, market trends, and changes in the average vehicle size, plus an increased availability of MASH tested products becoming available to the Australian market.

For temporary barriers, all contracts signed post 1 January 2022 shall use MASH temporary safety devices. While all contracts signed before 1 January 2022 may continue to use NCHRP 350 temporary safety barrier products until practical/physical completion.

Safety barrier systems with a legacy status continue to provide the level of service at which they were originally tested.

Temporary products with legacy status are listed in Table 19.

**Table 19 – Temporary products – legacy status**

<b>Product name</b>	<b>Supplier</b>	<b>Acceptance conditions date</b>	<b>Product photo</b>
ABSORB 350 Terminal	Australian Construction Products	<i>16 Dec 21</i>	
ARMORZONE Plastic Water Filled Barrier System	Ingal Civil Products	<i>16 Dec 21</i>	
JL-D-0850 Stuer-Egghe 'Julietta' TMA	J1-LED Intelligent Transport Solutions	<i>16 Dec 21</i>	
QUADGUARD CZ Crash Cushion	Ingal Civil Products	<i>16 Dec 21</i>	
SLOPED END Concrete Terminal – Temporary	Public Domain	<i>16 Dec 21</i>	
UNIVERSAL TAU-II Crash Cushion – Temporary	Australian Construction Products	<i>16 Dec 21</i>	